



# Williams Products, Inc

1750 Maplelawn

Troy, MI. 48084

Toll Free: 800-521-9594 Phone: 248-643-6400

Fax: 248-643-7117

## Everlastic® Masonry Anchor Gaskets

### Description

Self Stick, closed cell, Neoprene Gasket perforated & cut to dimensions of anchor back plate.

### Features

Custom Fabricated to match anchor size. Self stick, pressure sensitive adhesive allows simple and easy installation. Economical, Flexible, compressible, Resilient, Non-Absorbent, Closed Cell Rubber.

### Available Sizes

Nominal 1/8" Thick, supplied in panels perforated to size of anchor. Availability varies with size & quantity.

### Typical Physical Properties

Property	Typical Values
Polymer Base	CR/EPDM/SBR
Density (nominal)	7 +/-2 PCF
Compression/Deflection @ 25%	2 to 5 psi.
Ultimate Tensile Strength (Typical)	100 psi.
Elongation (Typical)	175%
Water Absorption (by weight)	5% Max.
Accelerated Aging (7 days @ 158°F)	
Appearance Change	None
Flexibility (180° bend w/out cracking)	Pass
Change in Compression / Deflection	+/- 30%
Flame Resistance	Pass
Odor	No objectionable odor
K Factor	0.30
Service Temperature	
Low	-70°F
High	220°F
High Intermittent	250°F

