



Williams Products, Inc

1750 Maplelawn

Troy, MI. 48084

Toll Free: 800-521-9594 Phone: 248-643-6400

Fax: 248-643-7117

Product Index DIVISION 3 CONCRETE

Bearing Pads

Com-Pad 100	Masticated Rubber
Bear-Pad 200	Cross Laminated with oriented fibers
Fab-Pad 300	Laminated, rubber and ductile fabric
1200 Series	Commercial Grade Dense Neoprene
AASHTO Grade Neoprene	Conforms to AASHTO requirements, 2500 PSI tensile strength

Rubber Waterstop

Compounds	Neoprene, Styrene-Butadiene-Rubber(SBR)
Sizes(widths)	6" & 9"
Profiles	Dumbbell(DB) and Centerbulb(CB)

Rubber "J" Gate Seals

Hi Tensile Neoprene Williams Compound # 1025

Expansion Joints

Econ-O-Foam	CCPE
EJ-2000	XL Polyolifin
NN-1, 1040 Series	Closed Cell Neoprene
1300 Series	Concrete Gray Sponge Rubber
1400 Series	Open Cell Neoprene (Vibration Isolation)

DIVISION 4 MASONRY

Column Isolation	
Column Boxboard	Coated Corrugated
Econ-O-Foam	CCPE
EJ-2000	XL Polyolifin

CMU Control Joints (Vertical)

Slot Seal Standard, Wide Flange, Block Seal
Hard rubber cross shape, shear keys in sash blocks

Weatherite R, Everlastic® M-CJ

Compressible Filler to seal Michigan Control Joints

Econ-O-Foam for Bond Break in core
Compressible to accommodate movement

CMU Expansion Joint (Horizontal)

Fill gap at top of wall
Expand-O-Foam

EVA 200G

Air Seal Gasket

1056 Joint Filler

Partition Closures

Close off gap between wall and deck (flat or fluted)

Special Fabrications

EVA 200

EPDM, 3000 Series

Fire Rated

Dyna Shield Ceramic Fiber Joint Filler

Vapor Barrier

MWM-40

Masonry Wall Membrane

Flashing

MF-40

Self Stick, Rubberized Asphalt

EPDM Membrane

Available by special order

Neoprene Membrane

Available by special order

PVC

10 mil to 56 mil

Available by special order

Anchor Gaskets

Self-stick, CC Neoprene

Thermal and moisture break behind anchors

Brick Expansion Joints

Neo Seal IV

Neoprene profile allows maximum movement

M-CJ

Self-stick, CC Rubber Joint Filler

Econ-O-Foam

Filler is inherent bond breaker for most sealants

Coping Gaskets

Special shapes

Variety of Materials

Brick Vents

Williams-Goodco PVC Brick Vents

Ventilates and equalizes pressure within cavity

Sizes, 2 - 1/4", 2 - 3/4", 3 - 5/8"

Colors, Standard Gray, We can dye to match mortar color



We do not guarantee the applicability or accuracy of this information or the suitability of our products for any given situation. The products discussed are sold without warranty, expressed or implied. Buyer assumes all responsibility for any loss or damage arising from the handling or use of our products, whether done in accordance with directions or not. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent.