



Williams Products, Inc

1750 Maplelawn
Troy, MI. 48084
Toll Free: 800-521-9594 Phone: 248-643-6400
Fax: 248-643-7117

Everlastic® COM-PADS CP-100

Description:

Black, fiber reinforced, dense rubber. Molded from masticated rubber compound. A durable dense rubber with excellent compressive strength, hardness, tear resistance and cold weather flexibility. "Green Product" molded from masticated rubber using discarded tires.

Uses:

Bearing Pads, Shims, Bumpers, Skid Pads, Roof Pads, etc.

Availability:

Thickness from 1/8" to 1"

Widths up to 60"

Lengths up to 100"

Available in cut parts and profiles

Typical Physical Properties:

Property	Typical Values	Test Method
Hardness (Shore A)	82 ± 5 Durometer	ASTM D-2240
Tensile Strength		ASTM D-412 Die C
Parallel to grain	750 psi	
Perpendicular to grain	350 psi	
Tear Strength		ASTM D-624 Die B
Parallel to grain	150 PPI	
Perpendicular to grain	300 PPI	
Elongation		ASTM D-412
Parallel to grain	15%	
Perpendicular to grain	45%	



We do not guarantee the applicability or accuracy of this information or the suitability of our products for any given situation. The products discussed are sold without warranty, expressed or implied. Buyer assumes all responsibility for any loss or damage arising from the handling or use of our products, whether done in accordance with directions or not. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent.